

# Influence of Iodine Pressure on the Growth of $\text{CuIn}_{1-x}\text{Ga}_x\text{Se}_2$ Thin Films Obtained by Close-Spaced Vapor Transport “CSVT”

Dayane Habib<sup>1</sup>, Roy Al Asmar<sup>1</sup>, Ziad El Helou<sup>1</sup>, Georges El Haj Moussa<sup>1,2</sup>

<sup>1</sup>Department of Physics, Faculty of Sciences II, Lebanese University, Jdeidet, Lebanon; <sup>2</sup>Centre Electronique et Micro-Opto-électronique de Montpellier (CEM2), Faculté Sciences et Techniques du Languedoc, Université de Montpellier II, Montpellier, France.

Email: dayane\_habib@yahoo.fr

Received July 24<sup>th</sup>, 2013; revised September 6<sup>th</sup>, 2013; accepted September 21<sup>st</sup>, 2013

Copyright © 2013 Dayane Habib *et al.* This is an open access article distributed under the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

## ABSTRACT

We present the results concerning photovoltaic materials  $\text{CuIn}_{1-x}\text{Ga}_x\text{Se}_2$  thin films, which were obtained by close-spaced vapor transport “CSVT”. The influence of the iodine pressure on the growth of  $\text{CuIn}_{1-x}\text{Ga}_x\text{Se}_2$  thin films was studied. The thin films were characterized by Energy Dispersive Spectrometry (EDS), Scanning Electron Microscope (SEM), hot point probe method, X-Ray Diffraction (XRD), Photoluminescence, and Optical response (Photoconductivity). At high pressure, the deposition rate was very important. The films were relatively thick and homogeneous with large grains dimensions. These films are formed of crystals placed in a preferential orientation depending on the plan (112). At low pressure, the films were thin and inhomogeneous with relatively small grains. These films of crystals didn't have preferential orientation.

**Keywords:** Chemical Vapor Deposition;  $\text{CuIn}_{1-x}\text{Ga}_x\text{Se}_2$ ; Thin Films; Chalcopyrite; Photovoltaic

## 1. Introduction

Chalcopyrite semiconductors  $\text{CuInSe}_2$ ,  $\text{CuGaSe}_2$  and their solid solution are well known as promising candidates for the fabrication of thin film heterojunctions for photovoltaic application. A conversion efficiency of 20% was reported for solar cells based on  $\text{Cu}(\text{In,Ga})\text{Se}_2$  [1]. Several processes are available for commercial application: Flash Evaporation [2], MOCVD [3], Electrodeposition [4], rf Sputtering [5], Coevaporation [6], Spray Pyrolysis [7], Selenization [8], rapid thermal processing (RTP) [9] or Close-Spaced Vapor Transport “CSVT”.

In this paper, we study the influence of the iodine pressure on the growth of  $\text{CuIn}_{1-x}\text{Ga}_x\text{Se}_2$  thin films obtained by the “CSVT” method. Energy Dispersive Spectrometry (EDS) and X-ray Diffraction (XRD) were used to calculate the compositions and lattice parameters of the films. Scanning Electron Microscope (SEM) enabled us to check their quality (grains size and morphology). Photoluminescence and photoconductivity allowed us to check their optical properties.

## 2. Experiment

The “CSVT” method needs a very simple and inexpensive reactor (**Figure 1**) described in [10]. It consists of a vertical quartz tube, with an inner diameter of about 20 mm, and a length of 10 - 20 cm, attached to a vacuum system. At the bottom of this reactor, there was a silice support on which the  $\text{CuIn}_{1-x}\text{Ga}_x\text{Se}_2$  source (chip with a thickness  $e = 1$  mm prepared from grains powder  $< 5 \mu\text{m}$  under a pressure of  $5 \times 10^3 \text{ kg/cm}^2$ ) [11] is putted. A soda lime glass substrate plate was set above the source at a close distance ( $0.5 \text{ mm} < d < 3 \text{ mm}$ ), by means of a ring spacer of quartz glass. The transport reagent, composed of iodine grains, was located at the upper part of the substrate. The complete system was installed on an external SiC rod. The source temperature depends on the electric voltage applied to this SiC heating element, the quartz plate thickness of ring spacer, and the distance  $d'$  between the reactor and the heating element. The substrate temperature is a function of the source temperature, the distance  $d$  between the source and the substrate, and the




Figure 1. Schematic diagram of the “CSVT” reactor.

gases pressure inside the reactor.

The reaction begins when iodine vaporizes and invades the tube; the pressure of the iodine was determined by the temperature ( $t_{cp}$ ) of the coldest point in the tube [11], generally at the level of the top.

The iodine vapor pressure ( $P_{I_2}$ ) (Figure 2) was calculated from the following equation:

$$\log_{10} P = (-0.2185 A/K) + B \quad (1)$$

where  $P$  is the pressure expressed in Torr,  $K$  is the temperature in Kelvin, and  $A$  is the molar heat of vaporization in calories per gram mole ( $A = 13056.6$  and  $B = 9.237273$ ).

Iodine decomposes and reacts with the chip surface by etching. The gaseous elements are transported to the substrate, slightly colder than the source (about  $50^\circ\text{C}$  to  $100^\circ\text{C}$ ). These elements settle and reconstitute the material.

### 3. Results and Discussion

Two series of  $\text{CuIn}_{1-x}\text{Ga}_x\text{Se}_2$  ( $0 \leq x \leq 1$ ) compound thin films corresponding to two values of the iodine pressure were studied. The vapor iodine pressure is varied by varying the temperature ( $t_{cp}$ ) of the coldest point in the tube ( $30^\circ\text{C}$  corresponding to  $P_{I_2} = 0.66$  Torr and  $70^\circ\text{C}$  to 8.31 Torr) (Figure 2). At low iodine pressure ( $t_{cp} = 30^\circ\text{C}$ ,  $P_{I_2} = 0.66$  Torr), the films obtained are thin (Table 1) and inhomogeneous. Two different zones were observed. The first is at the center, formed by melted selenium and crystals. The second, is the area around the center formed by well oriented crystals following a several preferential directions ((112), (220), (204), (316), (116)) indicated by X-ray spectra (Figure 3(a)).

At high pressure ( $P_{I_2} = 8.31$  Torr) corresponding to  $t_{cp} = 70^\circ\text{C}$ , thick films (Table 1) were obtained during a shorter time of transport compared to the low pressure case. These films were homogeneous and formed by well

oriented crystals following the direction (112) (Figure 3(b)).

In both cases, the size of crystals increases with the proportion of gallium. The lattice parameters  $a$  and  $c$  vary only linearly with  $x$  (Figure 4). These values decrease as the gallium concentration increases [12-14], since the gallium atom is much smaller than that of Indium. In all cases,  $c/a$  ratio is found to be nearly 2.

The analysis of the chemical composition by EDS (Figure 5) shows the presence of a small quantity of




Figure 2. The iodine vapor pressure ( $P_{I_2}$ ) is shown as a function of the temperature. This curve was calculated using Equation (1).







Figure 3. X-ray diffraction patterns of  $\text{CuIn}_{1-x}\text{Ga}_x\text{Se}_2$ : (a)  $t_{cp} = 30^\circ\text{C}$ ,  $P_{I_2} = 0.66$  Torr; (b)  $t_{cp} = 70^\circ\text{C}$ ,  $P_{I_2} = 8.31$  Torr.

**Table 1. Thickness, conductivity type and deposition time of different  $\text{CuIn}_{1-x}\text{Ga}_x\text{Se}_2$  samples.**

$\text{CuIn}_{1-x}\text{Ga}_x\text{Se}_2$	x	$t_{cp} = 30^\circ\text{C}, P_{12} = 0.66 \text{ Torr}$			$t_{cp} = 70^\circ\text{C}, P_{12} = 8.31 \text{ Torr}$		
		Time of deposition (min)	Thickness ( $\mu\text{m}$ )	Conductivity type	Time of deposition (min)	Thickness ( $\mu\text{m}$ )	Conductivity type
$\text{CuInSe}_2$	0	30	4.2	p	20	6.80	p
$\text{CuIn}_{0.8}\text{Ga}_{0.2}\text{Se}_2$	0.2	30	6.3	p	20	7.50	p
$\text{CuIn}_{0.6}\text{Ga}_{0.4}\text{Se}_2$	0.4	30	4.3	p	20	9.97	p
$\text{CuIn}_{0.4}\text{Ga}_{0.6}\text{Se}_2$	0.6	30	5.4	p	20	9.44	p
$\text{CuIn}_{0.2}\text{Ga}_{0.8}\text{Se}_2$	0.8	30	13.2	p	20	24.2	p
$\text{CuInGaSe}_2$	1	30	15.6	p	20	29.80	p


**Figure 4. Lattice parameters (a and c) for  $\text{CuIn}_x\text{Ga}_{1-x}\text{Se}_2$ : (O)  $t_{cp} = 30^\circ\text{C}, P_{12} = 0.66 \text{ Torr}$  and (X)  $t_{cp} = 70^\circ\text{C}, P_{12} = 8.31 \text{ Torr}$ .****Figure 5. Composition of  $\text{CuIn}_x\text{Ga}_{1-x}\text{Se}_2$  thin films determined by EDS as a function of the source composition x:  $\blacktriangledown$  Cu,  $\bullet$  In,  $\blacktriangle$  Ga,  $\blacksquare$  Se ( $t_{cp} = 30^\circ\text{C}, P_{12} = 0.66 \text{ Torr}$ ), and  $\nabla$  Cu,  $\circ$  In,  $\triangle$  Ga,  $\square$  Se ( $t_{cp} = 70^\circ\text{C}, P_{12} = 8.31 \text{ Torr}$ ).**

iodine in the films prepared at high  $P_{12}$ , whereas iodine is not detected in those grown at low pressure. Iodine may be removed by annealing at  $100^\circ\text{C}$ . **Figure 6** shows the morphologies of the surface, showing that the sizes of crystals prepared at high  $P_{12}$  are bigger ( $10 \mu\text{m} < \Phi < 25 \mu\text{m}$ ). The crystals have a better orientation than those grown at low  $P_{12}$  ( $3 \mu\text{m} < \Phi < 10 \mu\text{m}$ ). This result shows

**Figure 6. Surfaces SEM micrographs of the films: (a)  $\text{CuInSe}_2$ ; (b)  $\text{CuGaSe}_2$  ( $t_{cp} = 30^\circ\text{C}, P_{12} = 0.66 \text{ Torr}$ ); (c)  $\text{CuInSe}_2$ ; (d)  $\text{CuGaSe}_2$  ( $t_{cp} = 70^\circ\text{C}, P_{12} = 8.31 \text{ Torr}$ ).**

that the growth with a high iodine pressure is better.

**Figures 7(a) and (c)** show the spectra of Photoluminescence at liquid Helium temperature (4.2 K) of the alloy  $\text{CuIn}_{1-x}\text{Ga}_x\text{Se}_2$  thin films ( $x = 0$  and  $x = 1$ ) prepared at high  $P_{I_2}$ . An increase in the gap value of the materials  $\text{CuIn}_{1-x}\text{Ga}_x\text{Se}_2$  as a function of the concentration of Ga was observed. The band gap energy value at room temperature is determined in analyzing our compounds by spectral Photoconductivity [15]. **Figures 7(b) and (d)**



**Figure 7.** ((a), (c)) Variation of PL dominant peak of  $\text{CuIn}_{1-x}\text{Ga}_x\text{Se}_2$  thin films ( $x = 0$  and  $x = 1$ ) prepared at high  $P_{I_2}$ ; (b, d) The spectra of Photoconductivity  $((\alpha h\nu)^2)$  as a function of  $(h\nu)$  of the  $\text{CuIn}_{1-x}\text{Ga}_x\text{Se}_2$  thin films ( $x = 0$  and  $x = 1$ ) prepared at high  $P_{I_2}$ .

illustrate the spectra of Photoconductivity  $((\alpha h\nu)^2)$  as a function of  $h\nu$  of the  $\text{CuIn}_{1-x}\text{Ga}_x\text{Se}_2$  thin films ( $x = 0$  and  $x = 1$ ) prepared at high  $P_{I_2}$ . These values are in good agreement with those found by Photoluminescence and in literature [15-17].

The band gap of the thin films which prepared at low iodine pressure ( $t_{ep} = 30^\circ\text{C}$ ,  $P_{I_2} = 0.66$  Torrs) could not be observed, caused probably by the present of the melted selenium, or the thin films prepared at these low pressure are not brilliant.

## 4. Conclusion

$\text{CuIn}_{1-x}\text{Ga}_x\text{Se}_2$  thin films at two different iodine pressures were studied. At high pressure, the deposition rate is very important. The films are relatively thick and homogeneous with large grains dimensions. These films are formed of crystals placed in a preferential orientation depending on the plan (112). At low pressure, the films are thin and inhomogeneous with relatively small grains. These films of crystals didn't have preferential orientation. The characterization by Photoluminescence and Photoconductivity allows us to determinate the band gap values of the thin films prepared at high  $P_{I_2}$  which vary from 1.02 eV to 1.68 eV. The band gap of the thin films prepared at low  $P_{I_2}$  is not observed, probably due to the present of the melted selenium, or the no brilliant thin films prepared at this low pressure.

## REFERENCES

- [1] I. Repins, M. A. Contreras, B. Egaas, C. DeHart, J. Scharf, C. L. Perkins, B. To and R. Noufi, "New World Record Efficiency for  $\text{Cu}(\text{In,Ga})\text{Se}_2$  Thin-Film Solar Cells beyond 20%," *Progress in Photovoltaics: Research and Applications*, Vol. 16, No. 3, 2008, pp. 235-239. <http://dx.doi.org/10.1002/ppp.822>
- [2] H. Sakata and N. Nakao, "Optical and Electrical Properties of Flash-Evaporated Amorphous  $\text{CuInSe}_2$  Films," *Solar Energy Materials and Solar Cells*, Vol. 63, No. 3, 2000, pp. 259-265. [http://dx.doi.org/10.1016/S0927-0248\(00\)00032-5](http://dx.doi.org/10.1016/S0927-0248(00)00032-5)
- [3] G. Orsal, N. Romain, M. C. Artaud and S. Duchemin, "Characterization of  $\text{CuGaSe}_2$  Thin Films Grown by MOCV," *IEEE Transaction on Electron Device*, Vol. 46, No. 10, 1999, pp. 2098-2102. <http://dx.doi.org/10.1109/16.792003>
- [4] S. Nakamura, S. Sugawara, A. Hashimoto and A. Yamamoto, "Influence of Annealing Temperature on the Properties of  $\text{Cu}(\text{In,Ga})\text{Se}_2$  Thin Films by Thermal Crystallization in Se Vapor," *Solar Energy Materials & Solar Cells*, Vol. 50, No. 1-4, 1998, pp. 25-30. [http://dx.doi.org/10.1016/S0927-0248\(97\)00097-4](http://dx.doi.org/10.1016/S0927-0248(97)00097-4)
- [5] I. Martil, J. Santamaria, G. Gonzalez Diaz and F. Sanchez Quesada, "Structural, Electrical, and Optical Properties of  $\text{CuGaSe}_2$  rf Sputtered Thin Films," *Journal of Applied*

- Physics*, Vol. 68, No. 1, 1990, pp. 189-193.  
<http://dx.doi.org/10.1063/1.347113>
- [6] S. H. Kwon, B. T. Ahn, S. K. Kim, K. H. Yoon and J. Song, "Growth of  $\text{CuIn}_3\text{Se}_5$  Layer on  $\text{CuInSe}_2$  Films and Its Effect on the Photovoltaic Properties of  $\text{In}_2\text{Se}_3/\text{CuInSe}_2$  Solar Cells," *Thin Solid Films*, Vol. 323, No. 1-2, 1998, pp. 265-269.  
[http://dx.doi.org/10.1016/S0040-6090\(97\)00928-0](http://dx.doi.org/10.1016/S0040-6090(97)00928-0)
- [7] K. T. Ramakrishna Reddy and R. B. V. Chalapathy, "Preparation and Properties of Sprayed  $\text{CuGa}_{0.5}\text{In}_{0.5}\text{Se}_2$  Thin Films," *Solar Energy Materials & Solar Cells*, Vol. 50, No. 1-4, 1998, pp. 19-24.  
[http://dx.doi.org/10.1016/S0927-0248\(97\)00096-2](http://dx.doi.org/10.1016/S0927-0248(97)00096-2)
- [8] J. H. Schon, V. Alberts and E. Burcher, "Sharp Optical Emissions from Cu-Rich, Polycrystalline  $\text{CuInSe}_2$  Thin Films," *Journal of Applied Physics*, Vol. 81, No. 6, 1997, pp. 2799-2802. <http://dx.doi.org/10.1063/1.364306>
- [9] S. S. Kulkarni, G. T. Koishiyev, H. Moutinho and N. G. Dhere, "Preparation and Characterization of  $\text{CuIn}_{1-x}\text{Ga}_x\text{Se}_{2-y}\text{S}_y$  Thin Film Solar Cells by Rapid Thermal Processing," *Thin Solid Films*, Vol. 517, No. 7, 2009, pp. 2121-2124.  
<http://dx.doi.org/10.1016/j.tsf.2008.10.128>
- [10] G. W. El Haj Moussa, Ariswan, A. Khoury, F. Guastavino and C. Llinarés, "Fabrication and Study of Photovoltaic Material  $\text{CuIn}_x\text{Ga}_{1-x}\text{Se}_2$  Bulk and Thin Films Obtained by the Technique of Close-Spaced Vapor Transport," *Solid State Communications*, Vol. 122, No. 3-4, 2002, pp. 391-396.  
[http://dx.doi.org/10.1016/S0038-1098\(02\)00100-X](http://dx.doi.org/10.1016/S0038-1098(02)00100-X)
- [11] A. Zouaoui, M. Lachab, M. L. Hidalgo, A. Chaffa, C. Llinares and N. Kesri, "Structural, Compositional and Photoluminescence Characteristics of  $\text{CuInSe}_2$  Thin Films Prepared by Close-Spaced Vapor Transport," *Thin Solid Films*, Vol. 339, No. 1-2, 1999, pp. 10-80.  
[http://dx.doi.org/10.1016/S0040-6090\(98\)00893-1](http://dx.doi.org/10.1016/S0040-6090(98)00893-1)
- [12] G. W. El Haj Moussa, M. Ajaka, M. El Tahchi, E. Eid and C. Llinares, "Ellipsometric Spectroscopy on Polycrystalline  $\text{CuIn}_{1-x}\text{Ga}_x\text{Se}_2$ : Identification of Optical Transitions," *Physica Status Solidi (a)*, Vol. 202, No. 3, 2005, pp. 469-475. <http://dx.doi.org/10.1002/pssa.200406934>
- [13] F. Guastavino, K. Zeaiter, L. Djellal, M. Abdelali and C. Llinares, "Photoluminescence Study of  $\text{Cu}(\text{Ga}_x\text{In}_{1-x})_3\text{Se}_5$  and  $\text{CuIn}_3(\text{S}_x\text{Se}_{1-x})_5$  Crystals with  $0 \leq x \leq 1$ ," *Solid State Phenomena*, Vol. 67-68, 1999, pp. 427-432.  
<http://dx.doi.org/10.4028/www.scientific.net/SSP.67-68.427>
- [14] Ariswan, G. El Haj Moussa, M. Abdelali, F. Guastavino and C. Llinares, "Structural, Optical and Electrical Properties of the Ordered Vacancy Compound  $\text{CuIn}_3\text{Se}_5$  Thin Films Fabricated by Flash Evaporation," *Solid State Communications*, Vol. 124, No. 10-11, 2002, pp. 391-396.  
[http://dx.doi.org/10.1016/S0038-1098\(02\)00603-8](http://dx.doi.org/10.1016/S0038-1098(02)00603-8)
- [15] H. Zachmann, S. Heinker, A. Braun, A. V. Mudryi, V. F. Gremenok, A. V. Ivaniukovich and M. V. Yakushev, "Characterisation of  $\text{Cu}(\text{In,Ga})\text{Se}_2$ -Based Thin Film Solar Cells on Polyimide," *Thin Solid Films*, Vol. 517, No. 7, 2009, pp. 2209-2212.  
<http://dx.doi.org/10.1016/j.tsf.2008.10.132>
- [16] J. H. Schön, V. Alberts and E. Bucher, "Structural and Optical Characterization of Polycrystalline  $\text{CuInSe}_2$ ," *Thin Solid Films*, Vol. 301, No. 1-2, 1997, pp. 115-121.  
[http://dx.doi.org/10.1016/S0040-6090\(97\)00060-6](http://dx.doi.org/10.1016/S0040-6090(97)00060-6)
- [17] H. Miyake, T. Haginoya and K. Sugiyema, "THM Growth and Characterization of  $\text{CuGa}_x\text{In}_{1-x}\text{Se}_2$  Solid Solutions," *Solar Energy Materials and Solar Cells*, Vol. 50, No. 1-4, 1998, pp. 51-56.  
[http://dx.doi.org/10.1016/S0927-0248\(97\)00117-7](http://dx.doi.org/10.1016/S0927-0248(97)00117-7)